

	TYPE	Unit	LF 187MTD-Bi		LF 270MTD-Bi		LF 137 MTD-D		LF 187 MTD-D		LF270MTD-D		LF 137 MTD-M		LF 187 MTD-M		LF270MTD-M	
射出系統 Injection Unit	料軸直徑 Screw Diameter	mm	35	40	40	45	22	25	35	40	40	45	22	25	35	40	40	45
	射出重量 Shot Weight (PS)	gram	155	203	203	257	44	56	155	203	203	257	44	56	155	203	203	257
	射出壓力 Injection Pressure	kg/cm <sup>2</sup>	2357	1804	1804	1425	3599	2787	2357	1804	1804	1425	3599	2787	2357	1804	1804	1425
	理論射出容積 Theoretical Shot Volume	cm <sup>3</sup>	173	226	226	286	49	63	173	226	226	286	49	63	173	226	226	286
	射出行程 Injection Stroke	mm	180		180		130		180		180		130		180		180	
	射出率 Injection Rate	cm <sup>3</sup> / sec	105	138	138	174	41	53	105	138	138	174	41	53	105	138	138	174
	射出速度 Injection Speed	mm / sec	110		110		110		110		110		110		110		110	
	可塑化能力 Plasticization (Hydraulic Motor)	kg / hr	51	67	67	85	20	26	51	67	67	85	20	26	51	67	67	85
鎖模系統 Mold Lock Unit	直壓缸數 Number of Clamping Cylinder Drive	pc	2		2		4		4		4		4		4		4	
	閉模力 Clamping Force	ton	180		270		150		180		270		150		180		270	
	開模行程 Opening Stroke	mm	650		800		550		650		800		550		650		800	
	最小模厚 Minimum Mold Thickness	mm	200		300		200		200		300		200		200		300	
	機柱間隔 Tie Bar Clearance (HxV)	mm	635X385		960X510		455X455		505X505		560X560		455X455		505X505		560X560	
	頂出行程 Ejector Stroke	mm	105		150		95		105		150		95		105		150	
其他 Other	馬達 Motor Pump (Servo Motor & Piston Pump)	hp	25+25		30+30		20+20		20+20		30+30		20+20		20+20		30+30	
	電熱容量 Heater Capacity	kW	11.5X2		15X2		5X2		11.5X2		15X2		5X2		11.5X2		15X2	
	油箱容量 Oil Tank Capacity	L	600		800		400		600		800		400		600		800	
	機械重量 Machine Weight	ton	11.3		15.8		5.5		11.3		15.8		5.5		11.3		15.8	
	機械尺寸 Machine Size(L×W×H)	mm	5530X1450X2200		6625X1600X2430		4940X1550X2060		5530X1425X2200		6625X1600X2430		4940X1550X2060		5530X1425X2200		6625X1600X2430	