

VR

90t ~ 270t
Vertical Injection
Molding Type



ITEM 項目	TYPE 機型	Unit 單位	LF 87VR				LF 187VR		LF 270VR			
			A	B	C	D	A	B	A	B		
INJECTION UNIT 射出系統	Screw Diameter 料軸直徑	mm	22	25	28	30	40	45	45	50		
	Shot Weight (PS) 射出重量	gram	44	56	72	81	203	257	314	387		
	Injection Pressure 射出壓力	kg/cm ²	3616	2800	2232	1945	1805	1430	1930	1569		
	Theoretical Shot Volume 理論射出容積	cm ³	49	63	80	91	226	286	349	431		
	Injection Stroke 射出行程	mm	130				180		220			
	Injection Rate 射出率 / HB	cm ³ /sec.	45 / 64	58 / 83	73 / 104	84 / 120	125 / 175	158 / 222	190 / 190	235 / 235		
	Injection Speed 射出速度 / HB	mm/sec.	120 / 170				100 / 140		120 / 120			
	Plasticization 可塑化能力	kg/hr	20	26	33	38	67	85	85	105		
	Nozzle Contact Force 射嘴接觸力	ton	7.7				8.8		8.8			
	MOLD LOCK UNIT 鎖模系統	Number of Cylinder Drive 直壓缸數	Pc.	1								
		Clamping Force 閉模力	ton	90				180		270		
		Opening Stroke 開模行程	mm	300				400		450		
Minimum Mold Thickness 模厚大小		mm	200				300		350			
Maximum Daylight 總行程		mm	500				700		800			
Platen Dimension (H×V) 模板尺寸		mm	530×390				555×490		600×560			
Locating Ring Diameter 定位環直徑		mm	100				100 ~ 120		100 ~ 120			
Ejector Stroke 頂出行程		mm	60				100		100			
Ejector Force 頂出力		ton	6.7				6.7		6.7			
OTHER 其他		Motor 馬達	hp	20				30		40		
	HB Servo Motor 伺服馬達	hp	20				30		40			
	Heater Capacity 電熱容量	kW	5				8		11			
	Oil Tank Capacity 油箱容量	L	200				500		600			
	Machine Weight 機械重量	ton	2.8				8		12			
Machine Size 機械尺寸 (L×W×H)	mm	2600×2000×3900				2800×2100×4500		3600×2300×5900				

■ Specifications are subject to change without prior notice.
本公司保有變更設計之權利，規格如有更改恕不另行通知

■ Special Specification ordering is acceptable.
本公司亦接受特殊規格之訂製